




Earth inspection pits



Lightweight inspection pit

Description	Weight each	Part No.
Lightweight inspection pit with grey lid	1.80kg	PT205
Lightweight inspection pit with black (unbranded) lid	1.80kg	PT309-FU

Accessories

Description	Weight each	Part No.
5 hole earth bar	0.40kg	PT004
6mm Allen key	0.03kg	AK005

The lightweight inspection pit weighs only 1.8kg yet is load rated to 5,000kg. It has a lockable lid and improved working area compared to the concrete inspection pit.

An integral earth bar is available as an optional extra.

Manufactured from high-performance polymer, the lightweight pit is UV stable and chemically resistant.

Lightweight inspection pit with concrete lid

Description	Weight each	Part No.
Lightweight inspection pit with concrete lid	7.50kg	PT110

Accessories

Description	Weight each	Part No.
5 hole earth bar	0.40kg	PT004
M8 x 100mm lg mild steel 'J' bolt lifting hook	0.04kg	JH100
M8 x 60 stainless steel Allen caphead screw (2 per lid)	0.03kg	AS100

New to the range is a lightweight inspection pit with a concrete lid. Suitable for use in pedestrianised and light vehicular areas, the pit is load rated to 1,200kg.

The lid can be locked in place, if required (order 2 x AS100 Allen caphead screws).

Concrete inspection pit

Description	A B C Dimensions	Weight each	Part No.
Concrete inspection pit	320mm x 192mm x 146mm	30kg	PT005

Accessories

Description	Weight each	Part No.
5 hole earth bar	0.40kg	PT006
7 hole earth bar	0.58kg	PT007

The concrete inspection pit is load rated to 4,500kg and is suitable for most types of earthing and lightning protection installations.

It is not suitable for use in areas where high load, small wheel vehicles are used. The Lightweight inspection pit (PT205) is recommended for this type of application.